



**T340PO  
Penetrating Oil**



**Section 1: Chemical Product and Company Identification**

**Manufacturer / Supplier:** Shrader Canada Limited  
**Address:** 830 Progress Court, Oakville, Ontario L6L 6K1  
**Revision Date:** 12/14/2011  
**Product Use:** Penetrant  
**Chemical Family:** Mixture

**Section 2: Composition/Information on Ingredients**

<b>Component Name:</b>	<b>%</b>	<b>LD50 and LC50</b>	<b>ACGIH TWA</b>	<b>Ecotoxicity - Aquatic Toxicity</b>
Distillates (Petroleum), hydrotreated middle 64742-46-7	60-100	Inhalation LC50 Rat:4.6 mg/L 4h Oral LD50 Rat:7400 mg/kg Dermal LD50 Rabbit:2000 mg/kg	Not available	Not Available
Petroleum gases, liquified 68476-85-7	10-30	Not Available	= 1000 ppm TWA	Not Available
2-Butoxyethanol 111-76-2	1-5	Inhalation LC50 Rat:2.21 mg/L 4h Dermal LD50 Rabbit:220 mg/kg Dermal LD50 Rat:2270 mg/kg Inhalation LC50 Rat:450 ppm 4h Oral LD50 Rat:470 mg/kg	= 20 ppm TWA	LC50 (24 h) goldfish: 1650 mg/L. Cond: LC50 (96 h) bluegill: 1490 mg/L. Cond: static LC50 (24 h) water flea: 1720 mg/L
Xylene (mixture of isomers) 1330-20-7	0.5-1.5	Oral LD50 Rat:4300 mg/kg Inhalation LC50 Rat:5000 ppm 4h Dermal LD50 Rabbit:1700 mg/kg	= 100 ppm TWA =150 ppm STEL	LC50 (96 h) fathead minnow: 13.4 mg/L. Cond: flow-through LC50 (96 h) rainbow trout: 8.05 mg/L. Cond: flow-through LC50 (96 h) bluegill: 16.1 mg/L. Cond: flow-through EC50 (48 h) water flea: 3.82 mg/L EC50 (24 h) Photobacterium phosphoreum : 0.0084 mg/L

## Section 2: Composition/Information on Ingredients

Ethyl benzene 100-41-4	0.1-1.0	Dermal LD50 Rabbit:15354 mg/kg Inhalation LC50 Rat:17.2 mg/L 4h Oral LD50 Rat:3500 mg/kg	= 100 ppm TWA =125 ppm STEL	LC50 (96 h) bluegill: 150.0 mg/L. Cond: static LC50 (96 h) fathead minnow: 9.09 mg/L. Cond: flow-through LC50 (96 h) rainbow trout: 14.0 mg/L. Cond: static EC50 (48 h) water flea: 2.1 mg/L EC50 (30 min) Photobacterium phosphoreum : 9.68 mg/L
---------------------------	---------	---	--------------------------------	---

## Section 3: Hazards Identification

<b>Ingestion:</b>	Ingestion of small amounts during normal handling are not likely to cause injury. Ingestion of this product may cause nausea, vomiting and diarrhea. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
<b>Inhalation:</b>	High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and headache to unconsciousness.
<b>Skin Contact:</b>	Skin irritant.
<b>Eye Contact:</b>	Direct contact causes eye irritation. Symptoms will include pain, redness and tearing. Vapours will irritate the eyes.
<b>Chronic Effects:</b>	Chronic overexposure to 2-Butoxyethanol may cause liver, kidney and blood damage. Chronic overexposure to solvents such as Xylene can cause nervous system damage.

## Section 4: First Aid Measures

<b>Ingestion:</b>	Do not induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness, is unconscious or is convulsing. Drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Obtain medical attention immediately.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If breathing is difficult give oxygen. If not breathing give artificial respiration and get medical attention immediately.
<b>Skin Contact:</b>	Remove contaminated clothing and launder before reuse. Wash with soap and water. Seek medical attention if irritation persists.
<b>Eye Contact:</b>	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses if any after the initial flushing and then continue flushing. Get medical attention if irritation persists.

## Section 5: Fire Fighting Measures

<b>Flash Point (°C):</b>	>= 100 °C (Liquid Component)
<b>Flame Projection:</b>	< 100 cm. Flashback.
<b>NFPA Classification:</b>	Aerosol, Level 3
<b>Lower Explosive Limit:</b>	Not Available
<b>Upper Explosive Limit:</b>	Not Available
<b>Autoignition Temp. (°C):</b>	Not Available

### **Sensitivity to Mechanical Impact:**

Contents under pressure. Protect against physical damage.

**Conditions of Flammability:**

Flammable. Contents under pressure. Containers can build up pressure if exposed to heat (fire). Vapours are heavier than air and may travel or be moved along the ground to an ignition source at locations distant from material handling. Sprayed product will project a flame on contact with an ignition source.

**Sensitivity to Static Discharge:**

Take precautionary measures against static discharges, such as bonding and grounding when dispensing.

**Hazardous Combustion:**

Oxides of carbon, sulfur, nitrogen, phosphorous and other unidentified organic compounds.

**Extinguishing Media:**

Alcohol foam or water fog for large fires. Carbon dioxide or dry chemical for small fires. Use water spray to cool fire exposed containers and prevent bursting. Do not use a direct stream of water.

## Section 6: Accidental Release Measures

**Leak or Spill Procedures:**

Contain spilled material. Avoid contamination of natural waterways. Wear suitable protective clothing. Follow applicable explosion and fire precautions during the response. Stop the spill at the source when safe to do so. For large spills, dike the area to prevent spreading. Pump excess to a salvage container. Absorb residues and small spills with a non-flammable absorbent material and collect adsorbate for disposal. For large quantities refer to the environmental ministry.

## Section 7: Handling and Storage

**Handling Procedures:**

Flammable. Keep away from heat, spark, flame and other sources of ignition. Do not use on hot vehicles. Use with adequate ventilation. Avoid breathing vapours or mist. Avoid skin and eye contact. Wear all appropriate personal protective equipment during use. Use good personal hygiene. Avoid smoking, eating and drinking during use. Wash with soap and water after handling. Containers of this material may contain hazardous residues when emptied.

**Storage Requirements:**

Keep away from children. Store in a cool, dry, well-ventilated area. Storage temperatures should not exceed 40°C. Keep from freezing.

## Section 8: Exposure Controls / Personal Protection

<b>Respiratory:</b>	Not normally required. If the TLV is exceeded, a NIOSH-approved respirator is advised.
<b>Gloves:</b>	Neoprene. Nitrile gloves.
<b>Eyewear:</b>	Safety glasses. Contact lenses should not be worn. They may contribute to the severity of the injury.
<b>Clothing:</b>	Sufficient clothing to prevent skin contact.
<b>Ventilation:</b>	Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted.
<b>Other protective equipment:</b>	Emergency showers and eyewash facilities should be nearby. The selection of personal protective equipment will vary depending on the conditions of use.

## Section 9: Physical and Chemical Properties

<b>Physical State:</b>	Aerosol
<b>Color:</b>	Not Available
<b>Odour:</b>	Not Available
<b>Vapour Density (Air=1):</b>	> 1

## Section 9: Physical and Chemical Properties

VOC %: 24.5 (Nominal)  
pH: Not Applicable  
Solubility in Water: Negligible  
Specific Gravity (H<sub>2</sub>O=1): 0.825 @ 15°C  
Viscosity: < 8 cSt @ 40°C

## Section 10: Stability and Reactivity

### Conditions of Instability:

Stable at ambient temperatures and pressures.

### Hazardous Polymerization:

Hazardous polymerization will not occur.

### Hazardous Decomposition:

See hazardous combustion products.

### Incompatible Materials:

Avoid strong oxidizers (e.g H<sub>2</sub>O<sub>2</sub>, HNO<sub>3</sub>).

### Conditions of Reactivity:

Avoid excessive heat, sparks and open flame.

## Section 11: Toxicological Information

### Irritancy of Product:

Moderately irritating to eyes and skin.

### Sensitization to product:

Contains no known skin or respiratory sensitizers.

### Carcinogenicity:

Contains 0.1 - 1.0% by wt ethylbenzene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by IARC.

### Reproductive Effects:

Not Available

### Teratogenicity:

Xylene is reported to be fetotoxic.

### Mutagenicity:

Not Available

### Synergistic Products:

Xylene's potential for liver toxicity is enhanced by the presence of other solvents including ethanol.

## Section 12: Ecological Information

### Environmental:

This material contains substances that are expected to be harmful to aquatic organisms. See composition/information on ingredients.

### Biodegradability:

Not available.

## Section 13: Disposal Considerations

### Waste Disposal:

Contents under pressure. Do not puncture, incinerate or expose to heat even when empty. Reuse or recycling should be given priority over disposal under any circumstances. Do not dump unused contents into sewers, on the ground or into any body of water. Dispose of in accordance with municipal, provincial and federal regulations.

## Section 14: Transportation Information

**Road shipment:** AEROSOLS, Class 2.1, UN1950, ERG #126.

**Marine shipment:** UN1950, AEROSOLS, Class 2.1, EmS# F-D, S-U.

**Air Shipment:** Aerosols, Flammable, Class 2.1, UN1950, PI Y203/203.

**Exemption:** LTD QTY exemptions may be used if product is packaged in accordance with Schedule 1 of TDGR (Clear Language).

Product may be reclassified for air transportation if packaged in accordance to IATA regulations (i.e. Consumer Commodity, Class 9, ID 8000).

## Section 15: Regulatory Information

**WHMIS:** A B5 D2A D2B

**CEPA:** All components are listed on the Domestic Substances List (DSL).

**CPR Compliance:** This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

## Section 16: Other Information

**HMIS Rating:** 241B

**Prepared By:** Regulatory Compliance, Shrader Canada Limited

**Information Tel #:** 800-201-9486, 905-847-0222

**Information Fax #:** 905-847-5404

CANUTEC EMERGENCY: 613-996-6666