

T350FIC Fuel Injector Cleaner





Section 1: Chemical Product and Company Identification

Manufacturer / Supplier: Shrader Canada Limited

Address: 830 Progress Court, Oakville, Ontario L6L 6K1

Revision Date: 02/07/2012

Product Use: Fuel injector cleaner.
Chemical Family: Petroleum distillates

Section 2: Composition/Information on Ingredients

Component Name:	%	LD50 and LC50	ACGIH TWA	Ecotoxicity - Aquatic Toxicity
Stoddard Solvent 8052-41-3	30-60	Oral LD50 Rat: > 5000 mg/kg Dermal LD50 Rabbit: > 3000 mg/kg Inhalation LC50 Rat: > 1300 ppm 4h	= 100 ppm TWA	Not Available
RHT Base Oils Complex Mixture	30-60	Not Available	Not available	Not Available
Hydrocarbon solvent 64741-86-2	1-5	Not Available	Not available	Not Available
Polyether Amine HMIRC Reg 7117	1-5	Not Available	Not available	Not Available

Section 3: Hazards Identification

Ingestion: Ingestion of small amounts during normal handling are not likely

to cause injury. Larger amounts may cause effects similar to those described under inhalation. Ingestion of large amounts may cause

stomach irritation. Symptoms include nausea, vomiting and diarrhea. Aspiration into the lungs during swallowing or

subsequent vomiting may cause chemical pneumonitis, which can be

fatal.

Inhalation: High concentrations may cause respiratory irritation and central

nervous system depression with results ranging from dizziness and

headache to unconsciousness.

Skin Contact: Moderate to severe skin irritant, depending on duration of

exposure.

Eye Contact: May cause mild eye irritation. Symptoms will include pain, redness

and tearing. Vapours will irritate the eyes.

Product: T350FIC Revision: 2012-02-07 1 of 4

Section 3: Hazards Identification

Chronic Effects: Reports have associated repeated and prolonged occupational

overexposure to various organic solvents with internal organ,

brain and nervous system damage.

Section 4: First Aid Measures

Ingestion: Do not induce vomiting. Never give anything by mouth if victim

is rapidly losing consciousness, is unconscious or is convulsing. Drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Obtain medical

attention immediately.

Inhalation: If inhaled, remove to fresh air. If breathing is difficult give

oxygen. If not breathing give artificial respiration and get

medical attention immediately.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash with

soap and water. Seek medical attention if irritation persists.

Eye Contact: Immediately flush eyes with large amounts of water for at least

15 minutes, lifting upper and lower lids. Remove contact lenses if any after the initial flushing and then continue flushing.

Section 5: Fire Fighting Measures

Flash Point (°C): 43 (closed cup)
Flame Projection: Not Applicable.

NFPA Classification: Combustible Liquid, Class II

Lower Explosive Limit: Not Available Upper Explosive Limit: Not Available Autoignition Temp. (°C): Not Available

Sensitivity to Mechanical Impact:

Not Available

Conditions of Flammability:

Flammable when heated to temperatures above the flash point and on contact with an ignition source. Vapours are heavier than air and may travel or be moved along the ground to an ignition source at locations distant from material handling.

Sensitivity to Static Discharge:

Take precautionary measures against static discharges, such as bonding and grounding when dispensing.

Hazardous Combustion:

Carbon dioxide, carbon monoxide and other unidentified organic compounds. Oxides of nitrogen.

Extinguishing Media:

Alcohol foam or water fog for large fires. Carbon dioxide or dry chemical for small fires. Use water spray to cool fire exposed containers and prevent bursting. Do not use a direct stream of water.

Section 6: Accidental Release Measures

Leak or Spill Procedures:

Contain spilled material. Avoid contamination of natural waterways. Wear suitable protective clothing. Follow applicable explosion and fire precautions during the response. Stop the spill at the source when safe to do so. For large spills, dike the area to prevent spreading. Pump excess to a salvage container. Absorb residues and small spills with a non-flammable absorbent material and collect adsorbate for disposal. For large quantities refer to the environmental ministry.

Product: T350FIC Revision: 2012-02-07 2 of 4

Section 7: Handling and Storage

Handling Procedures:

Use with adequate ventilation. Avoid breathing vapours or mist. Avoid skin and eye contact. Use good personal hygiene. Avoid smoking, eating and drinking during use. Wash with soap and water after handling. Containers of this material may contain hazardous residues when emptied. Do not cut, weld, drill or grind on or near this container.

Storage Requirements:

Combustible liquid. Store in a cool area, away from all sources of heat, ignition and incompatibles. Storage temperatures should not exceed 35°C. Keep containers tightly closed when not in use.

Section 8: Exposure Controls / Personal Protection

Respiratory: Not normally required. If the TLV is exceeded, a NIOSH-approved

respirator is advised.

Gloves: Neoprene. Polyvinyl alcohol (PVA). Viton.

Eyewear: Safety glasses. Contact lenses should not be worn. They may

contribute to the severity of the injury.

Clothing: Sufficient clothing to prevent skin contact.

Ventilation: Sufficient mechanical ventilation to maintain exposures below the

TLV. General mechanical ventilation is not recommended as the sole

means of controlling exposure. Make-up air should always be

supplied to balance air exhausted.

Other protective equipment: Emergency showers and eyewash facilities should be nearby. The

selection of personal protective equipment will vary depending on

the conditions of use.

Section 9: Physical and Chemical Properties

Physical State: Liquid

Color: Clear light yellow Odour: Hydrocarbon odour

Vapour Density (Air=1): > 1 VOC %: 51

pH: Not Applicable
Solubility in Water: Negligible
Specific Gravity (H2O=1): 0.83 at 15°C
Viscosity: < 14cSt</pre>

Section 10: Stability and Reactivity

Conditions of Instability:

Stable at ambient temperatures and pressures.

Hazardous Polymerization:

Hazardous polymerization will not occur.

Hazardous Decomposition:

See hazardous combustion products.

Incompatible Materials:

Avoid strong oxidizers (e.g HOOH, HNO3).

Conditions of Reactivity:

Avoid excessive heat, sparks and open flame.

Section 11: Toxicological Information

Irritancy of Product:

Moderate to strong skin irritant, depending on duration of exposure. Respiratory irritant.

Sensitization to product:

Contains no known skin or respiratory sensitizers.

Product: T350FIC Revision: 2012-02-07 3 of 4

Carcinogenicity:

No components are listed as carcinogens by ACGIH, IARC, OSHA, or NTP. Contains 0.1 - 1.0% by wt naphthalene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by IARC.

Reproductive Effects:

Not Available

Teratogenicity:

Contains a component that contains xylene. Xylene is reported to be fetotoxic.

Mutagenicity:

Not Available

Synergystic Products:

Not Available

Section 12: Ecological Information

Environmental: This material contains substances that are expected to be harmful

to aquatic organisms.

Biodegradability: Not available.

Section 13: Disposal Considerations

Waste Disposal: Reuse or recycling should be given priority over disposal under

any circumstances. Destroy by incineration or biological treatment according to applicable legislation. Dispose of in accordance with

municipal, provincial and federal regulations.

Section 14: Transportation Information

Road shipment: PETROLEUM PRODUCTS, N.O.S., Class 3, UN1268, PG III, ERG #128.

Marine shipment: UN1268, PETROLEUM PRODUCTS, N.O.S., Class 3, PG III, EmS# F-E, S-E.

Air Shipment: Petroleum distillates, N.O.S. Class 3, UN1268, PG III, PI 309.

(Aromatic Naphtha),

Exemption: Not regulated for rail or road shipment based on Flammable Liquids

General Exemption (i.e. no subsidiary class, flash point > 37.8 °C and contained in one or more small means of containment).

Product may be reclassified for air transportation if packaged in accordance to IATA regulations (i.e. Consumer Commodity, Class 9,

ID 8000).

Section 15: Regulatory Information

WHMIS: B3, D2A, D2B

CEPA: All components are listed on the Domestic Substances List (DSL).

CPR Compliance: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Section 16: Other Information

HMIS Rating: 2*20B

Prepared By: Regulatory Compliance, Shrader Canada Limited

Information Tel #: 800-201-9486, 905-847-0222

Information Fax #: 905-847-5404

CANUTEC EMERGENCY: 613-996-6666

Product: T350FIC Revision: 2012-02-07 4 of 4